

Application

Semi-recessed luminaires with broad spread light distribution. The distinctive hand-blown, three-ply opal glass with concave interior surface provides a soft uniform light gradient.

Materials

Hand-blown three-ply opal glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Stainless steel screw clamps
Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 5.5 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	37.5 W
System wattage	44.0 W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	3456 lm
LED service life (L70)	60000 hrs

LED color temperature


4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:
BEGA Product:
Project:
Modified:

Available options

CP50177-	Ceiling pan (0-10V dimming down to 0.1%)
120V	
CP50177-	Ceiling pan (0-10V dimming down to 0.1%)
277V	



Semi-recessed ceiling luminaire · Opal glass				
	LED	A	B	C
B50177	37.5 W	10 ³ / ₈	3	2 ³ / ₈

