# Application

A versatile family of luminaires, the symmetric light distribution version is designed to wash wall surfaces. These luminaires are an excellent lighting tool for efficient, indirect illumination of interior spaces.

### Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy Pure anodized aluminum reflector surface

NRTL listed to North American Standards, for interior use only

Weight: 2.1 lbs.

#### Electrical

Operating voltage 120-277V AC
Minimum start temperature -40° C
LED module wattage 10.5 W
System wattage 12.0 W
Controllability 0-10V dimmable

Color rendering index Ra > 90 Luminaire lumens 970 lm LED service life (L70) 60000 hrs

# LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

#### Finish

Select the desired material finish by using appropriate code number as suffix.

#### Available colors

White (.1) Palladium (.4)

Velvet black (.5)

Type:

**BEGA Product:** 

**BEGA** 

Project: Modified:

# Included (available for pre-shipment)

B19542 Narrow opening wiring box





Wall washer · Symmetric				
	LED	Α	В	С
B50180	10.5 W	77/8	2 <sup>5</sup> / <sub>8</sub>	47/8