

Application
A versatile family of luminaires, the asymmetric light distribution version is intended to indirectly illuminate ceilings or archways, while also subtly illuminating the wall surface. These luminaires are an excellent lighting tool for efficient, indirect illumination of interior spaces.

Materials
Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Pure anodized aluminum reflector surface
NRTL listed to North American Standards, for interior use only
Weight: 3.7 lbs.


Electrical
Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 16.5 W
System wattage 19.2 W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 90
Luminaire lumens 1784 lm
LED service life (L70) 60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)
BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
Select the desired material finish by using appropriate code number as suffix.

Available colors
White (.1) Palladium (.4)
Velvet black (.5)

Type:
BEGA Product:
Project:
Modified:



Wall washer · Asymmetric				
	LED	A	B	C
B50200	16.5 W	10 1/4	3	6 1/8

