

**Application**  
A versatile family of luminaires, the asymmetric light distribution version is intended to indirectly illuminate ceilings or archways, while also subtly illuminating the wall surface. These luminaires are an excellent lighting tool for efficient, indirect illumination of interior spaces.

**Materials**  
Clear safety glass  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Pure anodized aluminum reflector surface  
**NRTL** listed to North American Standards, for interior use only

**Weight:** 6.4 lbs.

**Electrical**  
Operating voltage 120-277V AC  
Minimum start temperature -30° C  
LED module wattage 33.6 W  
System wattage 41.0 W  
Controllability 0-10V, TRIAC, and ELV dimmable  
Color rendering index Ra > 90  
Luminaire lumens 2927 lm  
LED service life (L70) 60000 hrs


**LED color temperature**  
4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
Select the desired material finish by using appropriate code number as suffix.

**Available colors**  
White (.1) Palladium (.4)  
Velvet black (.5)

Type:  
BEGA Product:  
Project:  
Modified:



| Wall washer · Asymmetric |        |                                |                               |                               |
|--------------------------|--------|--------------------------------|-------------------------------|-------------------------------|
|                          | LED    | A                              | B                             | C                             |
| B50201                   | 33.6 W | 12 <sup>5</sup> / <sub>8</sub> | 4 <sup>1</sup> / <sub>8</sub> | 7 <sup>3</sup> / <sub>8</sub> |

