

Application

This luminaire is designed to illuminate rooms, stairways, or hallways while creating an intriguing contrast between the luminaire and the mounting surface. The hand-blown, three-ply opal glass distributes diffuse light uniformly throughout a space.

Materials

Hand-blown opal glass
Aluminum housing
Stainless steel screw clamps
Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 2.1 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	8.4W
System wattage	12.0W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	570lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired trim ring material finish by using appropriate code number as suffix.

Available colors

White (.1) Stainless steel (.2)

Type:

BEGA Product:

Project:

Modified:



Available options

CP50523 Ceiling Pan (0-10V dimmable down to 0.1%)

Recessed ceiling luminaire · Opal glass

		LED	A	B
B50523	ADA	8.4 W	7 ¹ / ₈	2 ³ / ₈

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805)684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2025 Updated 07/11/25