

Application

Hand-blown, three-ply opal glass covers the recessed opening and, despite its very shallow projection, illuminates the room and mounting surface uniformly. The lateral illumination on the finished surface produces a floating effect.

Materials

- Hand-blown opal glass
- Aluminum housing
- Stainless steel screw clamps
- Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 7.1 lbs.

Electrical

- | | |
|---------------------------|----------------------------|
| Operating voltage | 120-277VAC |
| Minimum start temperature | -20° C |
| LED module wattage | 28.1 W |
| System wattage | 33.0 W |
| Controllability | 0-10V dimming down to 0.1% |
| Color rendering index | Ra > 90 |
| Luminaire lumens | 2197 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature


- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:
BEGA Product:
Project:
Modified:

Available options

- CP12124 Ceiling Pan (0-10V dimmable down to 0.1%)
- CP12124-SC Ceiling Pan for Suspended Ceiling (0-10V dimmable down to 0.1%)



Semi-recessed ceiling and wall luminaire · Opal glass				
		LED	A	B
B50529	ADA	28.1 W	13 1/2	2 3/8

