

Application

Hand-blown, three-ply opal glass covers the recessed opening and, despite its very shallow projection, illuminates the room and mounting surface uniformly. The lateral illumination on the finished surface produces a floating effect.

Materials

Hand-blown opal glass
Aluminum housing
Stainless steel screw clamps
Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 10.4 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	43.7 W
System wattage	50.0 W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	3200 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:

BEGA Product:

Project:

Modified:

Available options

CP50526-120V	Ceiling pan - 120V Only (0-10V dimmable down to 0.1%)
CP50526-277V	Ceiling pan - 277V Only (0-10V dimmable down to 0.1%)



Semi-recessed ceiling and wall luminaire · Opal glass				
		LED	A	B
B50530	ADA	43.7 W	17 ¹ / ₈	2 ³ / ₈

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2025 Updated 07/11/25