

Application

This recessed downlight's unique beauty and versatility is enhanced by the choice of four matte interior finishes combined with a velvet black trim finish. These finishes may be chosen to complement a wide array of interior spaces. A subtle hint of colored light on the outside edge of the beam spread results from the internally reflected light. The result is an eye-catching and elegant lighting effect.

Materials

Clear UV-stabilized acrylic diffuser
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 1.0 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	10.0 W
System wattage	12.0 W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	757 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired interior finish by using appropriate code number as suffix.

Available colors

White (.1)	Matte aluminum (.2)
Matte brass (.4)	Matte copper (.6)

Type:


BEGA Product:

Project:

Modified:

Available options

CP50576-120V	Ceiling pan - 120V only (0-10V dimmable down to 0.1%)
CP50576-277V	Ceiling pan - 277V only (0-10V dimmable down to 0.1%)



Downlight · STUDIO LINE · Velvet black				
	LED	□	A	B
B50576	10.0 W	65°	5 1/8	3

