

Application

Wall luminaires with up and down light output, ideal for highlighting columns or other architectural features. This family of luminaires with partially frosted crystal glass creates beautiful accents on the wall surface and adds sparkle to the space.

Materials

Partially frosted pressed crystal glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Pure anodized aluminum reflector surface

NRTL listed to North American Standards, for interior use only

Weight: 4.9 lbs.

Electrical

Operating voltage120-277V AC
Minimum start temperature-30° C
LED module wattage16.2 W
System wattage20.0 W
Controllability0-10V, TRIAC, and ELV dimmable
Color rendering indexRa > 90
Luminaire lumens1803 lm
LED service life (L70)60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors


White (.1)Stainless steel (.2)

Type:

BEGA Product:

Project:

Modified:



Wall luminaire · Light output on two sides					
	LED	A	B	C	D
B50601	16.2 W	5	6 ³ / ₈	6 ³ / ₈	3

