

Application

A wall washer luminaire with up and down light distribution. High lumen output and excellent glare control makes this luminaire well suited for illumination of tall interior walls or columns. Arranged individually or in groups, this wall luminaire creates visual interest in space while providing significant vertical and horizontal illumination.

Materials

Clear safety glass
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Pure anodized aluminum reflector surface
Silicone optic with excellent high temperature and UV stability
NRTL listed to North American Standards, for interior use only

Weight: 4.6 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	16.2 W
System wattage	20.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	1838 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors


White (.1)	Velvet black (.5)
------------	-------------------

Type:

BEGA Product:

Project:

Modified:



Wall washer · Light output on two sides					
	LED	A	B	C	D
B50603	16.2 W	5	10 ³ / ₄	6 ³ / ₈	3

