

Application

This pendent features thick-walled crystal glass, adding sparkle and visual interest to a room while the inner frosted section provides glare control and minimizes direct view of the LED source.

Materials

Partially frosted pressed crystal glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Galvanized zinc-plated mounting bracket
Pure anodized aluminum reflector surface
Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, for interior use only

Weight: 5.3 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	11.5 W
System wattage	14.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	1170 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

White (.1)	Stainless steel (.2)
------------	----------------------

Type:

BEGA Product:

Project:

Modified:



Pendant luminaire · Crystal glass

	LED	A	B	C
B50613	11.5 W	5 ³ / ₈	5 ³ / ₄	120

