

## Application

This pendant features thick-walled crystal glass, adding sparkle and visual interest to a room while the inner frosted section provides glare control and minimizes direct view of the LED source.

## Materials

Partially frosted pressed crystal glass  
Marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
Galvanized zinc-plated mounting bracket  
Pure anodized aluminum reflector surface  
Silicone optic with excellent high temperature and UV stability

**NRTL** listed to North American Standards, for interior use only

**Weight:** 6.8 lbs.

## Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30°C
LED module wattage	17.0W
System wattage	21.0W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	1682 lm
LED service life (L70)	60000hrs

### LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

## Finish

Select the desired material finish by using appropriate code number as suffix.

### Available colors

White (.1)                      Stainless steel (.2)



Pendant luminaire · Crystal glass

	LED	A	B	C
<b>B50614</b>	17.0W	7	67/8	120

Type:

BEGA Product:

Project:

Modified: