

Application

This recessed trimless downlight installs flush with the ceiling plane. A subtle hint of colored light on the outside edge of the beam spread results from the internally reflected light. The result is an eye-catching and elegant lighting effect.

Materials

Die-cast aluminum
Composite installation housing
Silicone optic with excellent high temperature and UV stability
Pure anodized aluminum reflector surface with matte finish

NRTL listed to North American Standards, for interior use only

Weight: 2.7 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	14.9W
System wattage	21.0W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	1893lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired interior finish by using appropriate code number as suffix.

Available colors


Matte aluminum (.2)	Matte brass (.4)
Matte copper (.6)	

Type:

BEGA Product:

Project:

Modified:



Downlight · STUDIO LINE · White

	LED	□	A	B
B50683	14.9W	36°	6 ³ / ₄	4 ⁷ / ₈

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805)684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2024 Updated 08/02/24