

Application

This recessed trimless downlight installs flush with the ceiling plane. A subtle hint of colored light on the outside edge of the beam spread results from the internally reflected light. The result is an eye-catching and elegant lighting effect.

Materials

- Die-cast aluminum
- Composite installation housing
- Silicone optic with excellent high temperature and UV stability
- Pure anodized aluminum reflector surface with matte finish

NRTL listed to North American Standards, for interior use only

Weight: 2.7 lbs.

Electrical

- | | |
|---------------------------|----------------------------|
| Operating voltage | 120-277VAC |
| Minimum start temperature | -20° C |
| LED module wattage | 14.9W |
| System wattage | 21.0W |
| Controllability | 0-10V dimming down to 0.1% |
| Color rendering index | Ra > 90 |
| Luminaire lumens | 1893lm |
| LED service life (L70) | 60000hrs |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired interior finish by using appropriate code number as suffix.

Available colors


- | | |
|---------------------|------------------|
| Matte aluminum (.2) | Matte brass (.4) |
| Matte copper (.6) | |

Type:

BEGA Product:

Project:

Modified:



Downlight · STUDIO LINE · Velvet black				
	LED	<input type="checkbox"/>	A	B
B50686	14.9W	36°	6 7/8	5

