

Application

This compact luminaire is characterized by high light output and minimal recessed depth. The trimless, thick-walled crystal glass brings sparkle and added interest to any ceiling surface, while the inner frosted sections provide glare control.

Materials

Partially frosted pressed crystal glass
Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
Aluminum ceiling mounted driver box
Pure anodized aluminum reflector surface
Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, for interior use only

Weight: 5.3 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	17.2 W
System wattage	20.0 W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	1753 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:


BEGA Product:

Project:

Modified:

Available options

CP50376 Ceiling pan (0–10V dimming only)



Semi-recessed downlight · Crystal glass				
	LED	□	A	B
B50689	17.2 W	50°	8	4 ³ / ₄