

Application

The partially frosted, crystal glass provides glare control while adding sparkle to any space. The simple shape makes these ideal for any architectural style. Coupled with the latest LED technology, this luminaire is an efficient, long service life lighting solution for spaces where architectural interest is a part of the lighting requirement.

Materials

- Partially frosted pressed crystal glass
- Die-cast aluminum
- White or black connecting cable
- Pure anodized aluminum reflector surface
- NRTL listed to North American Standards, for interior use only
- Weight: 4.4 lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage11.5 W
- System wattage13.0 W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 90
- Luminaire lumens1196 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Stainless steel (.2)
- Chrome (.3)

Type:

BEGA Product:

Project:

Modified:



Pendant · Crystal glass				
	LED	A	B	C
B50700	11.5 W	5 1/4	7 1/8	84

