

Application

The partially frosted, crystal glass provides glare control while adding sparkle to any space. The simple shape makes these ideal for any architectural style. Coupled with the latest LED technology, this luminaire is an efficient, long service life lighting solution for spaces where architectural interest is a part of the lighting requirement.

Materials

- Partially frosted pressed crystal glass
- Die-cast aluminum
- White or black connecting cable
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, for interior use only

Weight: 5.7 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	16.8 W
System wattage	20.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	1634 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Stainless steel (.2)
- Chrome (.3)

Type:

BEGA Product:

Project:

Modified:



Pendant · Crystal glass				
	LED	A	B	C
B50701	16.8 W	6	8 ³ / ₄	84

