

Application

Accent luminaires for the private home and garden. These unshielded luminaires create a pleasant light effect and are provided with an earth spike for flexible installation as design parameters change over time. Low voltage magnetic transformer required for operation.

Materials

High temperature silicone gasket
Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.6 lbs.

Electrical

Operating voltage	12VAC
Minimum start temperature	-40° C
LED module wattage	1.9W
System wattage	2.5W
Controllability	Non-Dimming
Color rendering index	Ra > 80
Luminaire lumens	171 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Synthetic housing provided in standard BEGA Graphite. Custom colors not available.

Type:

BEGA Product:

Project:

Modified:


Available options

- AMB Amber LED

Available accessories

- B536 Low voltage magnetic transformer · 300W

See individual accessory spec sheet for details.



Garden luminaire with earth spike · Unshielded · 12V AC				
	LED	A	B	C
B55010	1.9W	2 ³ / ₄	13 ¹ / ₂	7 ⁵ / ₈

