

Application

Designed for down lighting atriums, canopies, passages, and other interior and exterior locations featuring a symmetric narrow beam distribution.

Materials

- Clear safety glass
- Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
- 316 grade stainless steel
- High temperature silicone gasket
- Stainless steel screw clamps
- Aluminum ceiling mounted driver box
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 0.5 lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage4.2W
- System wattage6.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 90
- Luminaire lumens327 lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:


BEGA Product:

Project:

Modified:

Available options

- FROFrosted lens
- FSCFusing
- HXLHex cell louver
- SLLSolite lens



Downlight · Narrow beam				
	LED		A	B
B55821	4.2 W	27°	3 1/8	2 1/2

