

Application

Designed for down lighting atriums, canopies, passages, and other interior and exterior locations featuring a symmetric narrow beam light distribution.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Stainless steel screw clamps
- Aluminum ceiling mounted driver box
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 0.5 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	4.2 W
System wattage	6.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	327 lm
LED service life (L70)	60000 hrs

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:


BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
FRO	Frosted lens
FSC	Fusing
HXL	Hex cell louver
MGU	Marine grade undercoat
RAL	RAL finish
SLL	Solite lens



Downlight · Narrow beam

	LED		A	B
B55921	4.2 W	28°	3 1/8	2 1/2

