

Application
Designed for down lighting atriums, canopies, passages, and other interior and exterior locations featuring a symmetrical wide beam light distribution.

Materials
Luminaire housing constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Clear safety glass
Reflector made of pure anodized aluminum
High temperature silicone gasket
Stainless steel screw clamps
Galvanized steel rough in ceiling pan with through wiring box

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 1.4 lbs


Electrical	
Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	12.7 W
System wattage	15.5 W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 85
Luminaire lumens	1066 lumens (3000K)
Lifetime at Ta = 15° C	360,000 h (L70)
Lifetime at Ta = 35° C	270,000 h (L70)

LED color temperature
4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3 (EXPRESS)**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :



LED recessed ceiling downlight · wide beam					
	LED	β	A	B	C
55 926	12.7 W	86 °	5 5⁄8	3 1⁄4	18

β = Beam angle

Type:
BEGA Product:
Project:
Modified:

