Application

Designed for down lighting atriums, canopies, passages, and other interior and exterior locations featuring a symmetric wide beam light distribution.

Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

High temperature silicone gasket Stainless steel screw clamps

Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 2.1 lbs. Electrical

LED module wattage 18.1 W System wattage 22.0 W Color rendering index Luminaire lumens

Ra > 80 1327 lm 60000 hrs LED service life (L70)

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ) Silver (SLV) White (WHT) Natural Bronze (NTB) RAL:

CUS:

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish

Digital addressable lighting interface DALI 55928

FRO Frosted lens FSC Fusing HXL Hex cell louver


MGU Marine grade undercoat RAL RAL Classic, matte finish

SLL Solite lens

Included (available for pre-shipment)

CP5927 Ceiling pan





Downlight · Wide beam

	LED	β	А	В	С	
B55928	18.1 W	86°	6 ⁷ / ₈	31/2	18	