

Application

Semi-recessed ceiling luminaire with partially frosted crystal glass and symmetric wide beam light distribution designed for downlighting atriums, passages and other interior and exterior locations.

Materials

Partially frosted pressed crystal glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Stainless steel screw clamps
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 1.4 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	8.7 W
System wattage	11.0 W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 80
Luminaire lumens	632 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:


Modified:

Available options

FRO	Frosted lens
FSC	Fusing
HXL	Hex cell louver

Included (available for pre-shipment)

CP5923 Ceiling pan



Downlight · Symmetric				
	LED	A	B	C
B55942	8.7W	4 ¹ / ₂	2 ³ / ₄	18

