

Application

Semi-recessed ceiling luminaire with partially frosted crystal glass and symmetric wide beam light distribution designed for downlighting atriums, passages and other interior and exterior locations.

Materials

Partially frosted pressed crystal glass  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Stainless steel screw clamps  
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 4.2 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	18.1 W
System wattage	22.0W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 80
Luminaire lumens	1241 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:


Modified:

Available options

DALI	Digital addressable lighting interface
FSC	Fusing
SLL	Solite lens

Included (available for pre-shipment)

CP5927	Ceiling pan
--------	-------------



Downlight · Symmetric			
	LED	A	B
B55944	18.1 W	7 1/4	3 1/2

