

Application

A compact ceiling mounted downlight with partially frosted crystal glass. The partially frosted crystal glass creates an additional vertical light component that supplements the downlight. These luminaires are designed for down lighting atriums, canopies, passages, and other interior and exterior locations.

Materials

Partially frosted pressed crystal glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 1.3 lbs.

Electrical

Operating voltage	24VDC (remote power supply req.)
Minimum start temperature	-40° C
LED module wattage	4.9W
System wattage	7.0W
Controllability	Non-Dimming
Color rendering index	Ra > 80
Luminaire lumens	492lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:
BEGA Product:
Project:
Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish


Available accessories

B19591 Remote driver box · Static white

See individual accessory spec sheet for details.

Included (available for pre-shipment)

B19538 Small opening wiring box



Surface mounted downlight · Symmetric · 24V DC			
	LED	A	B
B66050	4.9W	3 ³ / ₄	3 ⁵ / ₈

