

Application

Wall mount luminaire with asymmetric light distribution designed for the illumination of parking areas and roadways.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Silicone applied robotically to casting, plasma treated for increased adhesion
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Integral surge protector
- Galvanized zinc-plated mounting bracket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 66

Weight: 9.3 lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage31.5W
- System wattage37.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens4741 lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)

Silver (SLV)

Natural Bronze (NTB)

CUS:
- Bronze (BRZ)

White (WHT)

RAL:

Type:
BEGA Product:
Project:
Modified:

Available options

- CUS

DALI-2

FSC

MGU

NTB

RAL
- Custom finish


DALI dimming

Fusing

Marine grade undercoat

Natural bronze (premium finish)

RAL finish



Area/roadway wall luminaire · Asymmetric					
	LED	A	B	C	D
B66451	31.5W	10	2 ³ / ₈	16 ¹ / ₈	5 ¹ / ₈