

Application

Wall mount luminaire with asymmetric flat beam light distribution designed for the illumination of parking areas and roadways.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Silicone applied robotically to casting, plasma treated for increased adhesion
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Integral surge protector
- Galvanized zinc-plated mounting bracket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 66

Weight: 9.3 lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage23.6W
- System wattage29.0W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens3492lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:


BEGA Product:

Project:

Modified:

Available options

- 347V347V input
- CUSCustom finish
- FSCFusing
- MGUMarine grade undercoat
- RALRAL finish
- STPStep dimming (120V only)



Area/roadway wall luminaire · Asymmetric flat beam

	LED	A	B	C	D
B66456	23.6W	10	2 ³ / ₈	16 ¹ / ₈	5 ¹ / ₈