Application

Wall luminaires with directed narrow beam light distribution on two sides. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials

Clear safety glass

Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket

Mechanically captive stainless steel fasteners

Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 11.5lbs.

Electrical

Operating voltage 120-277V AC Minimum start temperature -30° C LED module wattage 25.0 W System wattage 29.0 W

Controllability 0-10V, TRIAC, and ELV dimmable

Color rendering index Ra > 80 Luminaire lumens 2465 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:

CUS:

Type:

**BEGA Product:** 

Project: Modified:

## Available options

CUS Custom finish

FSC Fusing

MGU Marine grade undercoat NTB Natural bronze (premium finish)

RAL RAL finish

## Available accessories


B79547 Surface mounted wiring box

See individual accessory spec sheet for details.

## Included (available for pre-shipment)

B19537 Narrow opening wiring box





Wall luminaire · Narrow beam upward · Narrow beam downward

	LED		Α	В	С	D	
B66519	25.0 W	18°	6	215/	77/0	15/	