

Application

Compact ceiling mounted downlight designed for down lighting atriums, canopies, passages, and other interior and exterior locations featuring a symmetric distribution.

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.2 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	4.9W
System wattage	7.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	532lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:

BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
FRO	Frosted lens
FSC	Fusing
HXL	Hex cell louver
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish
SLL	Solite lens



Surface mounted downlight · Wide beams				
	LED	β	A	B
B66977	4.9W	90°	5	4 ³ / ₈