

Application

Control up to 20 DALI-2 operating devices including luminaires or sensors. The Air Connector requires line voltage power input and receives a wired DALI-2 group connection. All configuration and control of this device communicates with the BEGA Connect Cloud via a Narrow Band IoT wireless connection.

Materials

Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy

Composite housing

Black connecting cable

High temperature silicone gasket

Mechanically captive stainless steel fasteners

Stainless steel hardware

Mounting hardware included

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 4.0 lbs.

EPA (Effective projection area): 0.2 sq. ft.

Electrical

Operating voltage 120-277VAC

Minimum start temperature -20°C

Controllability DALI-2

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)


Bronze (BRZ)

Silver (SLV)

White (WHT)

RAL:

CUS:



Air Connector · Pole mount

	A	B
B71297	4	9 ³ / ₈

Type:

BEGA Product:

Project:

Modified:

