

Application

Factory sealed recessed wall luminaire with asymmetric floodlight optics, designed to be installed in walls or other vertical or horizontal surfaces for both interior and exterior locations.

Materials

Clear safety glass with optical texture
Corrosion-resistant 304 grade stainless steel
Stainless steel screw clamps
Aluminum installation housing
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 12.8lbs.

Electrical

Operating voltage	24VDC (remote power supply req.)
Minimum start temperature	-40° C
LED module wattage	9.7 W
System wattage	13.0 W
Controllability	Non-Dimming
Color rendering index	Ra > 80
Luminaire lumens	453 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:

Modified:

Available options

FSC Fusing

Available accessories

B19580 Remote driver box · Static white
B19591 Remote driver box · Static white

See individual accessory spec sheet for details.

Included (available for pre-shipment)

BB7002LED Installation housing



Recessed wall luminaire · Asymmetric · 24V DC				
	LED	A	B	C
B77002	9.7 W	39 ³ / ₈	2 ¹ / ₈	4

