

Application
In-grade floodlight with asymmetric light distribution. This family of luminaires is resistant to foot traffic and is ideally suited for the illumination of architectural details or landscape features around the home and garden. Low voltage magnetic transformer required for operation.

Materials
Clear safety glass
Corrosion-resistant 304 grade stainless steel
High temperature silicone gasket
Composite installation housing
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 1.9 lbs.

Electrical

Operating voltage	12VAC
Minimum start temperature	-40° C
LED module wattage	3.0W
System wattage	4.2W
Controllability	Non-Dimming
Color rendering index	Ra > 90
Luminaire lumens	319lm
LED service life (L70)	60000hrs


LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Available accessories
B536 Low voltage magnetic transformer · 300W
See individual accessory spec sheet for details.



Garden floodlight · Asymmetric · 12V AC				
	LED	A	B	C
B77008	3.0W	4 ³ / ₈	2 ³ / ₄	4 ⁷ / ₈

