

Application
Flush in-grade small-scale symmetric floodlights. Designed to uplight trees, walls, columns, or signage from ground surfaces. Luminaires require a remote 24 V DC class 2 power supply suitable to operate at the intended LED wattage.

Materials
Clear safety glass
Corrosion-resistant 304 grade stainless steel
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 68

Weight: 1.8 lbs.

Electrical

LED module wattage	1.2 W
System wattage	2.0 W
Color rendering index	Ra > 80
Luminaire lumens	134 lm
LED service life (L70)	60000 hrs


LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Available accessories
B19591 Remote driver box · Static white
See individual accessory spec sheet for details.



In-grade luminaire · Symmetric · 24V DC					
	LED		A	B	C
B77017	1.2W	38°	3	1 ³ / ₄	2 ¹ / ₂

