

Application

Flush in-grade small-scale asymmetric floodlights. Designed for directional lighting, uplighting of trees, walls, columns, or signage from ground surfaces. Luminaires require a remote 24 V DC class 2 power supply suitable to operate at the intended LED wattage.

Materials

- Clear safety glass
- Corrosion-resistant 304 grade stainless steel
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 68

Weight: 3.1 lbs.

Electrical

Operating voltage	24VDC (remote power supply req.)
Minimum start temperature	-40° C
LED module wattage	3.0W
System wattage	5.8W
Controllability	Non-Dimming
Color rendering index	Ra > 80
Luminaire lumens	364 lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:


Project:


Modified:

Available accessories

- B19580 Remote driver box · Static white
- B19591 Remote driver box · Static white

See individual accessory spec sheet for details.



In-grade luminaire · Asymmetric · 24V DC					
	LED		A	B	C
B77019	3.0W	38°x35°	4 ⁵ / ₈	3 ¹ / ₈	3 ⁷ / ₈

