

Application

Flush in-grade small-scale location uplights. Designed for indicator or general area lighting. Luminaires require a remote 24 V DC class 2 power supply suitable to operate at the intended LED wattage.

Materials

- Clear safety glass with white ceramic coating
- Corrosion-resistant 304 grade stainless steel
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 68

Weight: 3.1 lbs.

Electrical

Operating voltage	24VDC (remote power supply req.)
Minimum start temperature	-40° C
LED module wattage	2.1 W
System wattage	4.0 W
Controllability	Non-Dimming
Color rendering index	Ra > 80
Luminaire lumens	74 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:


Project:

Modified:

Available accessories

- B19580 Remote driver box · Static white
- B19591 Remote driver box · Static white

See individual accessory spec sheet for details.



In-grade luminaire · Location Luminaire · 24V DC				
	LED	A	B	C
B77028	2.1 W	4 <sup>5</sup> / <sub>8</sub>	3 <sup>1</sup> / <sub>8</sub>	3 <sup>7</sup> / <sub>8</sub>

