

Application
In-grade location luminaires. These luminaires are designed to bear especially high pressure loads of up to 11,000 lbs from vehicles with pneumatic tires. The luminaires must not be used for traffic lanes where they are subject to horizontal pressure from vehicles braking, accelerating and changing direction.

Materials
Clear safety glass with white ceramic coating
Corrosion-resistant 304 grade stainless steel
High temperature silicone gasket
Stainless steel screw clamps
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 68

Weight: 28.0 lbs.

Electrical
Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 19.0 W
System wattage 22.0 W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 214 lm
LED service life (L70) 60000 hrs


LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Available options
NSL Non-skid lens



In-grade luminaire · Location luminaire			
	LED	A	B
B77073	19.0W	13	6 1/8

