

Application
In-grade asymmetric floodlight luminaires. These luminaires are designed to bear pressure loads up to 4400 lbs. from vehicles with pneumatic tires. The luminaires must not be used for traffic lanes where they are subject to horizontal pressure from vehicles braking, accelerating and changing direction.

Materials
Clear safety glass
316 grade stainless steel
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Fully potted waterstopper cable
Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 68

Weight: 14.8lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	36.2W
System wattage	42.6W
Controllability	0-10V dimming down to 1%
Color rendering index	Ra > 80
Luminaire lumens	3349lm
LED service life (L70)	60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Available options
FSC Fusing
NSL Non-skid lens

Included (available for pre-shipment)
B688 Installation housing



In-grade luminaire · Asymmetric					
	LED		A	B	C
B77116	36.2 W	30°x35°	13	16	10

