


Tools Required:

3mm hex key
4mm hex key
6mm hex key
Adjustable wrench

Protection Class: IP65

Weight: 22.0 lbs.


Dimensions

A: 25-5/8 "

B: 23-5/8 "


Notice to Installer for 77 120:

1. See page 2 for specific product safety warnings.
2. For pole top applications only.
3. Slip fits 3" O.D. poles only.
4. LED module and integral driver provided by BEGA.
5. Pole top luminaire supplied with 25 feet of cable to route through pole.
6. An 18" space above luminaire is required to change and maintain lens and luminaire.

77 120 - installation:

1. Loosen (4) 6mm hex screws on luminaire top and remove.
2. Install reflector disk and secure with (4) 4mm hex screws evenly.
3. Replace top and tighten (4) 6mm hex screws to secure.
4. Route the luminaire wiring through to the pole base and slip luminaire over the top of the pole.
5. Secure luminaire by tightening set screws on pole fitter, evenly.
6. Make supply wiring connections to luminaire wires in pole base:
MAIN VOLTAGE SUPPLY WIRE TO BLACK LUMINAIRE WIRE
NEUTRAL (COMMON) SUPPLY WIRE TO WHITE LUMINAIRE WIRE
GREEN GROUND WIRE TO GREEN LUMINAIRE WIRE

Relamping/Maintenance

No relamping necessary.

Accessories

Please refer to the appropriate accessory installation sheet for further instruction when applicable.

Replacement Parts

Description	Part No
Acrylic lens cylinder	150298.6
Lens gasket top	830774
Lens gasket lower	831075
LED Driver (120-277V)	75985-03
LED Module (3000K)	(x6) LED-0146/830
LED Module (4000K)	(x6) LED-0146/840

Lamp: 23.4W LED Module

Product Safety Warnings:

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED. SUITABLE FOR WET LOCATIONS.

MIN 90°C SUPPLY CONDUCTORS.

CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHÉRENTS. CONVIENT AUX EMPLACEMENTS MOUILLÉS.

LES FILS D'ALIMENTATION 90°C MIN.