

Application

Pole top luminaire with symmetric distribution. An unshielded diffuser creates a soft, uniform distribution and visual interest for pedestrian environments.

Materials

White UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Integral surge protector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 19.0lbs.

EPA (Effective projection area): 1.6 sq. ft.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	24.0W
System wattage	28.0W
Controllability	0-10V dimming down to 1%
Color rendering index	Ra > 80
Luminaire lumens	2525 lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish



Edge-lit pole-top luminaire · Symmetric

	LED	A	B
B77122	24.0W	20 ¹ / ₈	26 ¹ / ₈

