## Application

In-grade location luminaries. These luminaires are designed to bear pressure loads of up to 4400lbs from vehicles with pneumatic tires. The luminaires must not be used for traffic lanes where they are subject to horizontal pressure from vehicles braking, accelerating and changing direction.

### Materials

Clear safety glass with white ceramic coating Corrosion-resistant 304 grade stainless steel High temperature silicone gasket

Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 68

Weight: 1.8 lbs.

Electrical

LED module wattage 0.6 W
System wattage 1.0 W
Color rendering index Ra > 80
Luminaire lumens 28 lm
LED service life (L70) 60000 hrs

### LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

#### Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

**BEGA Product:** 

Project: Modified:

# Available accessories

B19580 Remote driver box ⋅ Static white B19591 Remote driver box ⋅ Static white See individual accessory spec sheet for details.







In-grade luminaire · Location luminaire · 24V DC

LED A B C
B77127 0.6W 3 13/4 21/2