


BEGA

Photometric Filename: 77135.ies

TEST: BE_77135
TEST LAB: BEGA
DATE: 6/26/2017
LUMINAIRE: 77 135
LAMP: 24W LED




Characteristics

IES Classification	Type V
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2408
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	86
Total Luminaire Watts	28
Ballast Factor	1.00
Upward Waste Light Ratio	0.03
Max. Cd.	613.1 (0H, 35V)
Max. Cd. (<90 Vert.)	613.1 (0H, 35V)
Max. Cd. (At 90 Deg. Vert.)	54.6 (2.3%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	124.6 (5.2%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)


Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	220.8	N.A.	9.2
FM (30-60)	633.6	N.A.	26.3
FH (60-80)	269.3	N.A.	11.2
FVH (80-90)	47.0	N.A.	2.0
BL (0-30)	220.8	N.A.	9.2
BM (30-60)	633.6	N.A.	26.3
BH (60-80)	269.3	N.A.	11.2
BVH (80-90)	47.0	N.A.	2.0
UL (90-100)	39.5	N.A.	1.6
UH (100-180)	26.7	N.A.	1.1
Total	2407.6	N.A.	100.0

BUG Rating B1-U2-G1



Mounting Height = 12 ft. (Pole 906HR)
Grid Spacing = 10 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

3/26/2018