

Application
Pole-top luminaire with shielded symmetric light distribution. The symmetric distribution is ideal for illuminating squares, plazas and other open areas.

Materials
Clear UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 22.0 lbs.

EPA (Effective projection area): 1.3 sq. ft.

Electrical	
Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	23.4 W
System wattage	27.0 W
Controllability	0-10V dimming down to 1%
Color rendering index	Ra > 80
Luminaire lumens	1697 lm
LED service life (L70)	60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors	
Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:
BEGA Product:
Project:
Modified:

Available options	
CUS	Custom finish
DALI-2	Digital addressable lighting interface
MGU	Marine grade undercoat
RAL	RAL finish



Pole-top luminaire · Symmetric			
	LED	A	B
B77142	23.4 W	25 ⁵ / ₈	23 ⁵ / ₈

