

Application

Pole top luminaire with asymmetric light distribution. The edge-lit source ensures visual comfort, while the unique interreflection of light in the clear diffuser creates visual interest. Ideal for illuminating pedestrian spaces such as plazas, walkways, and building entrances.

Materials

- Clear UV-stabilized acrylic diffuser
- Optically textured UV-stabilized acrylic diffuser
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Integral surge protector
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 19.0 lbs.

EPA (Effective projection area): 1.6 sq. ft.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage24.0 W
- System wattage28.0 W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens2390 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- |              |              |
|--------------|--------------|
| Black (BLK)  | Bronze (BRZ) |
| Silver (SLV) | White (WHT)  |
| RAL:         | CUS:         |

Type:


BEGA Product:

Project:

Modified:

Available options

- |     |                        |
|-----|------------------------|
| CUS | Custom finish          |
| FSC | Fusing                 |
| MGU | Marine grade undercoat |
| RAL | RAL finish             |



| Edge-lit pole-top luminaire · Asymmetric |        |        |        |
|------------------------------------------|--------|--------|--------|
|                                          | LED    | A      | B      |
| B77151                                   | 24.0 W | 20 1⁄8 | 26 1⁄8 |

