

Application
Pole-top luminaire with asymmetric wide beam light distribution. Ideal for illuminating perimeters of plazas, streets, and pathways while adding visual interest.

Materials
Clear UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 11.0lbs.

EPA (Effective projection area): 1.1 sq. ft.

Electrical
Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 31.0W
System wattage 36.0W
Controllability 0-10V dimming down to 1%
Color rendering index Ra > 80
Luminaire lumens 3134 lm
LED service life (L70) 60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
DALI-2 Digital addressable lighting interface
FSC Fusing
MGU Marine grade undercoat
RAL RAL finish



Pole-top luminaire · Asymmetric wide beam		
	LED	A B
B77165	31.0W	10 1/4 25 3/4

