

Application

Bollard with shielded, direct light for illuminating entrances, paths, and many areas of public and private spaces. These luminaires provide glare-free illumination with a high degree of visual comfort for uniform lighting of ground surfaces.

Materials

Optically textured UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Zinc plated carbon steel anchor bolts with template

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 10.1 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
Maximum ambient temperature 90° C
LED module wattage 7.6W
System wattage 11.0W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 90
Luminaire lumens 643lm
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

AMB Amber LED
CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL finish

Included (available for pre-shipment)

B79817 Anchorage kit



Bollard · Shielded · Single				
	LED	A	B	C
B77221	7.6W	7 1/2	39 1/2	11