

Application

Pathway luminaire with shielded light for use in the private sector. These luminaires are ideally suited for gardens, entryways, and for many applications on paths and terraces. Anchorage unit is intended for direct burial in concrete or soil. Low voltage magnetic transformer required for operation.

Materials

- Clear safety glass with matte finish
- Aluminum housing
- High temperature silicone gasket
- Galvanized steel anchorage

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 6.2 lbs.

Electrical

|                           |             |
|---------------------------|-------------|
| Operating voltage         | 12VAC       |
| Minimum start temperature | -40° C      |
| LED module wattage        | 4.2W        |
| System wattage            | 5.8W        |
| Controllability           | Non-Dimming |
| Color rendering index     | Ra > 90     |
| Luminaire lumens          | 156lm       |
| LED service life (L70)    | 60000hrs    |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

|                      |              |
|----------------------|--------------|
| Black (BLK)          | Bronze (BRZ) |
| Silver (SLV)         | White (WHT)  |
| Natural Bronze (NTB) | RAL:         |
| CUS:                 |              |

Type:

BEGA Product:

Project:

Modified:


Available options

|     |                                 |
|-----|---------------------------------|
| CUS | Custom finish                   |
| MGU | Marine grade undercoat          |
| NTB | Natural bronze (premium finish) |
| RAL | RAL finish                      |

Available accessories

|      |                                         |
|------|-----------------------------------------|
| B536 | Low voltage magnetic transformer · 300W |
|------|-----------------------------------------|

See individual accessory spec sheet for details.



| Garden bollard · Direct burial anchorage · 12V AC |      |       |        |   |
|---------------------------------------------------|------|-------|--------|---|
|                                                   | LED  | A     | B      | C |
| B77265                                            | 4.2W | 3 1/2 | 27 1/2 | 2 |

