

Application

Compact rectangular floodlight with mounting canopy and outrigger arm. Designed to illuminate architecture and signage. Pair with a variety of optical accessories.

Materials

Clear safety glass with optical texture
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
304 stainless steel outrigger arm
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 5.3 lbs.

EPA (Effective projection area): 0.5 sq. ft.

Electrical

Operating voltage 120, 220-240 OR 277 VAC
Minimum start temperature -30° C
LED module wattage 17.9 W
System wattage 20.4 W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 2456 lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

B548 Barn door shield
B70500 Glare shield · 180°
CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL finish



Floodlight · Wide beam						
	LED	□	A	B	C	D
B77552	17.9 W	74°x89°	6 1/2	27 5/8	2	7 1/2