

Application

Compact floodlight with mounting canopy for direct mounting to horizontal or vertical surfaces. Designed to illuminate architectural features, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

Materials

Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Pure anodized aluminum reflector
Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.0 lbs.

Electrical

Operating voltage 24VDC (remote power supply req.)
Minimum start temperature -40° C
LED module wattage 7.9W
System wattage 9.0W
Controllability Non-Dimming
Color rendering index Ra > 80
Luminaire lumens 888lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

AMB Amber LED
B70050 Elliptical spread lens
B70755 Glare shield · 180°
CUS Custom finish
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL finish


Available accessories

B19580 Remote driver box · Static white
B19591 Remote driver box · Static white

See individual accessory spec sheet for details.

Included (available for pre-shipment)

B19538 Small opening wiring box



Compact floodlight · Wide beam · 24V DC						
	LED	□	A	B	C	D
B77607	7.9W	47°	4 1/8	5 7/8	4 3/8	3 1/2

