

Application

Compact floodlight with mounting canopy for direct mounting to horizontal or vertical surfaces. Designed to illuminate architectural features, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector
- Silicone optic with excellent high temperature and UV stability
- Composite concentric ring louver

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 10.1 lbs.

EPA (Effective projection area): 0.5 sq. ft.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage48.2 W
- System wattage51.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 90
- Luminaire lumens3025 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)

Silver (SLV)

Natural Bronze (NTB)

CUS:
- Bronze (BRZ)

White (WHT)

RAL:

Type:

BEGA Product:

Project:

Modified:

Available options

- B70077

B70721

B70758

CUS

DALI

FSC

MGU

NTB

RAL
- Elliptical spread lens

Glare shield · 360°

Glare shield · 180°

Custom finish


Digital addressable lighting interface

Fusing

Marine grade undercoat

Natural bronze (premium finish)

RAL finish



Compact floodlight · Very narrow beam

	LED	□	A	B	C	D
B77639	48.2 W	10°	9 1⁄8	12	8 5⁄8	5 1⁄8

