

Application

Compact floodlight with mounting canopy for direct mounting to horizontal or vertical surfaces. Designed to illuminate architectural features, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector
- Silicone optic with excellent high temperature and UV stability
- Composite concentric ring louver

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 3.5 lbs.

EPA (Effective projection area): 0.3 sq. ft.

Electrical

Operating voltage	120, 220-240 OR 277 VAC
Minimum start temperature	-30° C
LED module wattage	9.0W
System wattage	9.8W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	675lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:


BEGA Product:

Project:

Modified:

Available options

B70075	Elliptical spread lens
B70712	Glare shield · 360°
B70756	Glare shield · 180°
CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish



Compact floodlight · Very narrow beam

	LED	□	A	B	C	D
B77680	9.0W	8°	5 1/2	8	5 1/2	3 7/8

